

Delta 4 Beam

The TÜV-tested and flexible d-flexx safety barrier "Delta" is an innovative and economic separation of pedestrian areas and trails.

Additionally to the 3 beams Delta safety barrier we now offer you two variants of the Delta barrier with four beams in height 1200 mm and 1600 mm. The Delta barrier in 1200 mm height with four beams offers a protection with a difference of only 329 mm to the ground for more protection

Due to the modular system a customized solution can always be supplied by means of individual cuttings.

The mounting material is always included in the scope of delivery of the d-flexx Safety Barrier Delta. The fischer ULTRACUT FBS II is the perfect powerful contrete screw for top installation comfort.



FACTS

| ART. NO | COMPONENTS |
|----------|-----------------------|
| 12000018 | Delta Bollard |
| 12000019 | Delta End post |
| 12000020 | Delta Cross post |
| 12000021 | Delta Middle post |
| 12000022 | Delta T-post |
| 12000023 | Delta Corner post |
| 12000024 | Delta End post |
| 12000025 | Delta Cross post |
| 12000027 | Delta T-post |
| 12000028 | Delta Corner post |
| 12000029 | Delta Standard beam |
| 12000030 | Delta Individual beam |



COMBINE WITH











CHARLIE

ECHO

DELTA 3 BEAM

JULIET